The Delphion Integrated View

Title: **JP11240970A2: POROUS MEMBRANE AND SEPARATOR USING THE SAM AND USED FOR BATTERY**

Derwent Title: Porous film for use as separator in batteries and portable electronic devices - has specific electrical resistance before and after heat processing and ion permeability interruption temperature [Derwent Record]

Country: **JP** Japan
Kind: **A**

Inventor: **NISHIYAMA SOJI**;
MATSUSHITA KIICHIRO;
ISHIZAKI SATORU;
WANO TAKASHI;



Assignee: **NITTO DENKO CORP**
News, Profiles, Stocks and More about this company

Published / Filed: **1999-09-07** / 1998-02-24

Application Number: **JP1998000042515**

IPC Code: **C08J 9/00;** C08K 5/20; H01M 2/16; C08L 23/02;

Priority Number: 1998-02-24 **JP1998199842515**

Abstract:

PROBLEM TO BE SOLVED: To provide a porous membrane having a low shutdown(SD)-initiating temperature and a large SD rate and useful as a separator for a battery.

SOLUTION: This porous membrane is formed from a mixture of a polyolefin with a substance which has a lower melting point than that of the polyolefin and is incompatible with the polyolefin. The substance comprises at least one of a resin having a viscosity-average mol.wt. of 100-10,000 and an aliphatic compound having 9-22 carbon atoms in the aliphatic chain. When the ion transmission-interrupting temperature of the porous membrane is set to a range of 105-130°C, and when the electric resistance of the porous membrane is measured on the basis of JIS C 2313, the electric resistance value of the porous membrane after a thermal treatment at 130°C for 0.6 sec is set to ⩾20 times an electric resistance before the treatment. Polypropylene and highly dense polyethylene wax may be used as the polyolefin and the substance, respectively.

Family: None

Forward References: **Go to Result Set:** Forward references (2)

PDF	Patent	Pub.Date	Inventor	Assignee	Title

	US6749961	2004-06-15	Nguyen; Khuy V.	Celgard Inc.	Shutdown battery separator made w a blend of polymer and oligomer
	US6586912	2003-07-01	Tsukamoto; Hisashi	Quallion LLC	Method and apparatus for amplitude limiting battery temperature spikes

Other Abstract Info: CHEMABS 131(14)186015K CHEMABS 131(14)186015K DERABS C1999-555112 DERABS C1999-555112

(19)

(11) Publication number: **11240**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **10042515**

(51) Intl. Cl.: **C08J 9/00** C08K 5/20 H01M 2/16

(22) Application date: **24.02.98**

(30) Priority:

(43) Date of application publication: **07.09.99**

(84) Designated contracting states:

(71) Applicant: **NITTO DENKO CORP**

(72) Inventor: **NISHIYAMA SOJI**
MATSUSHITA KIICHIRO
ISHIZAKI SATORU
WANO TAKASHI

(74) Representative:

(54) POROUS MEMBRANE AND SEPARATOR USING THE SAME AND USED FOR BATTERY

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a porous membrane having a low shutdown(SD)-initiating temperature and a large SD rate and useful as a separator for a battery.

SOLUTION: This porous membrane is formed from a mixture of a polyolefin with a substance which has a lower melting point than that of the polyolefin and is incompatible with the polyolefin. The substance comprises at least one of a resin having a viscosity-average mol.wt. of 100-10,000 and an aliphatic compound having 9-22 carbon atoms in the aliphatic chain. When the ion transmission-interrupting temperature of the porous membrane is set to a range of 105-130°C, and when the electric resistance of the porous membrane is

measured on the basis of JIS C 2313, the electric resistance value of the porous membrane after a thermal treatment at 130°C for 0.6 sec is set to ⩾20 times an electric resistance before the treatment. Polypropylene and highly dense polyethylene wax may be used as the polyolefin and the substance, respectively.